

#### (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

# (19) World Intellectual Property Organization International Bureau



### 

## (43) International Publication Date 5 February 2004 (05.02.2004)

#### **PCT**

## (10) International Publication Number WO 2004/012279 A2

(51) International Patent Classification7:

H01L 41/00

(21) International Application Number:

PCT/IL2003/000603

(22) International Filing Date: 23 July 2003 (23.07.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 10/206,717

25 July 2002 (25.07.2002) US

(71) Applicant (for all designated States except US): NANOMOTION LTD. [IL/IL]; P.O. Box 223, 20692 Yokneam (IL).


(72) Inventor; and

(75) Inventor/Applicant (for US only): GANOR, Ze'ev [IL/IL]; 13 Ben Shalom Street, 46408 Herzelia (IL).

- (74) Agents: FENSTER, Paul et al.; Fenster & Company, Intellectual Property 2002 Ltd., P.O. Box 10256, 49002 Petach Tikva (IL).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: HIGH RESOLUTION PIEZOELECTRIC MOTOR



(57) Abstract: A piezoelectric motor for moving and positioning a load, the motor comprising: a piezoelectric vibrator having a plurality of electrodes and a coupling surface which is pressed to a load; and a power supply selectively operable to electrify at least one vibrator electrode with time varying voltage to generate vibrations in the coupling surface that step the load to a desired position or to electrify at least one vibrator electrode with DC voltage to displace the coupling surface and move thereby the load to a desired position, which DC voltage the power supply maintains to maintain the load at the desired position.